



NOTES:
TECHNICAL REQUIREMENT
 1. THE DIMENSION OF JOINT FLANGE COMPLY WITH : ANSI B16.1 125PSI
 2. THE FACE TO FACE OF BODY COMPLY WITH : MSS SP-67

TECHNICAL DATA			
WORKING PRESSURE		150 PSI	
TEST PRESSURE	SEAT	165 PSI	
	SHELL	225 PSI	
WORKING TEMP.	EPDM	-22F TO 230F	
	NBR	-4F TO 179F	

Ref No.	Description	Material			Qty
		Ductile Iron Disc	Aluminum Bronze Disc	Stainless Steel Disc	
1	Gear Operator	Case, A126 Cl. B, Gear, ASTM A536 65-45-12			1
2	Bottom Plate	Ductile Iron, ASTM A536 65-45-12			1
3	Bottom Plate Screw	Steel, ASTM A283D A36			4
4	Bottom Plate O-ring	Rubber, ASTM D2000 NBR			1
5	Gasket	Steel			1
6	Bearing	Bronze ASTM B584 C83600			1
7	Lower Bushing	Bronze ASTM B584 C83600			1
8	Body	Ductile Iron, ASTM A536 65-45-12			1
9	Seat	Rubber, ASTM D2000 EPDM or NBR			1
10	Lower Shaft	Stainless, ASTM A582 S41600	Stainless, ASTM A582 S41600	Stainless, ASTM A276 S31600	1
11	Disc	Ductile Iron, ASTM A536 65-45-12 (Nickel Plated)	Aluminum Bronze, JIS H5114	Stainless, ASTM A351 CF8M	1
12	Taper Pin	Stainless, ASTM A564 S17400			3
13	Upper Shaft	Stainless, ASTM A582 S41600	Stainless, ASTM A582 S41600	Stainless, ASTM A276 S31600	1
14	Long Bushing	ASTM A584 C83600			1
15	Name Plate	Aluminum			1
16	Short Bushing	Bronze ASTM B584 C83600			4
17	O-ring	Rubber, ASTM D2000 EPDM			3
18	Key	Steel			2

Size	D1	D2	D3	D4	N2	D10	D6	N1	D7	D8	D9	L	L1	H1	H2	H3	t	K1	K2	G1	G2	G3	G4	G5	G6	G7
28	11.81	2.49	36.50	34.00	24	1-1/4-7UNC-2B	10.00	8	0.71	27.36	26.42	6.42	6.65	20.47	24.57	2.60	2.13	0.71	2.48	21.28	19.13	7.66	5.98	7.24	15.75	13.54
30	11.81	2.49	38.74	36.00	28	1-1/4-7UNC-2B	10.00	8	0.71	29.29	28.58	6.57	6.81	22.05	25.98	2.60	2.13	0.71	2.48	21.28	19.13	7.66	5.98	7.24	15.75	13.54
32	11.81	2.49	41.73	38.50	24	1-1/2-6UNC-2B	10.00	8	0.71	31.30	30.33	7.40	7.68	23.27	26.46	2.60	2.40	0.71	2.48	21.28	19.13	7.66	5.98	7.24	15.75	13.54
36	11.81	2.95	45.98	42.76	32	1-1/2-6UNC-2B	10.00	8	0.71	34.06	33.11	7.99	8.31	25.83	28.35	4.65	2.40	0.79	3.94	24.96	21.65	9.72	6.38	7.87	15.75	15.24
40	11.81	3.35	50.75	47.25	28	1-1/2-6UNC-2B	10.00	8	0.71	37.99	37.05	8.50	8.82	28.39	31.50	5.91	2.52	0.79	3.94	24.96	21.65	9.72	6.38	7.87	15.75	15.24
42	13.78	3.74	52.99	49.49	36	1-1/2-6UNC-2B	11.73	8	0.87	40.55	39.33	9.88	10.28	30.59	33.78	5.91	2.64	0.98	5.51	31.89	25.59	12.60	9.29	7.87	17.72	18.62
48	13.78	4.13	59.49	56.00	44	1-1/2-6UNC-2B	11.73	8	0.87	45.67	44.37	10.87	11.26	34.02	37.05	5.91	2.76	1.10	5.51	31.89	25.59	12.60	9.29	7.87	17.72	18.62



TITLE: U-BODY LARGE DIAMETER RESILIENT SEATED BUTTERFLY VALVE
 DATE: 1/24/2009 BY: PEA APP'D: KMC UNITS: IN SCALE: NONE REV DATE: 5-25-2010
 FILE: 752_28-48.DWG MODEL: 752 DWG NO: 752_28-48 REV: 1

REV 1: Added Al-Brz Disc Config

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION.