



Pressure Ranges

- 0 - 30 PSI
- 0 - 60 PSI
- 0 - 100 PSI
- 0 - 160 PSI
- 0 - 200 PSI
- 0 - 300 PSI

Ambient Temperature Limits:  
 -40 °F to 150 °F (-40 °C to 65 °C)  
 Process Temperature Limits:  
 -40 °F to 150 °F (-40 °C to 65 °C)  
 Case: 304SS  
 Bezel: 304SS  
 Lens: Polycarbonate  
 Dial: Aluminum  
 Tube: Ph Bz  
 Movement: Brass  
 Socket: Brass  
 Welding: Silver Alloy  
 Accuracy: ±1% (ANSI/ASME Grade 1A)  
 Enclosure: IP52  
 Recalibrator Screw: Standard



<b>FNW™</b>		4120 NE Columbia Blvd Portland, OR 97211 Phone (503)287-8383 Fax (503)281-9677
TITLE/DESCRIPTION Figure G, 4.5" Contractor Gauge Bottom Connection		
DATE: 9-24-2009	BY: PEA	NUMBER: <b>FNWG</b>
REV: 0	APVD: KNC	
CONFIDENTIAL AND PROPRIETARY INFORMATION BELONGING TO FNW VALVE, SUBMITTED FOR THE LIMITED PURPOSE OF PROVIDING INFORMATION ON PRODUCTS AND SYSTEMS. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.		
UNITS: INCHES	SCALE: NTS	PAGE 1 OF 1